



**SMM WEB SERVICE**

**SmmWs3 API**

*The information in this document is subject to change without notice.*

*This document contains information protected by copyright.  
No part of this document may be photocopied or reproduced in any form  
without prior written consent from San Marino Mail Italia S.r.l.*

*@Copyright 2026 San Marino Mail Italia.*

*All rights reserved.*

*Date Revised: Mon, 12th February 2026*

## TABLE OF CONTENTS

Tables Index.....	3
Document purpose.....	3
API description.....	3
Generate Token.....	5
Create Shipment.....	6
Get Label.....	12
Delete Label.....	14
Manifest.....	15
Document upload.....	16
Document Delete .....	19
Tracking .....	20
Annexes .....	22

## TABLES INDEX

## DOCUMENT PURPOSE

This document briefly describes how to interact with SMM SmmWs3 API. Also are described the operations (i.e. methods) that are exposed and response messages.

## API DESCRIPTION

The API exposes the following services:

- Generate Token\*
- Create Shipment and generate label
- Get Label
- Delete Label
- Manifest
- Upload document [Action: UPLOAD]
- Delete document [Action: DELETE]
- Tracking

The Generate Token service will provide a valid token, that must be provided to all the other services.

All data passed and received with the web-service is based on headers values and JSON strings and everything needs to be passed with **[POST]** method. To be able to use all the services (except Generate Token), it's mandatory to add the following headers in the call:

- Accept: application/json
- username: testusername
- token: {token}TEST-TOKEN-a0a2-47b0-b1ab-923d2ec4b8ce

If any of these mandatory headers is missing, the service will return an error response.

## GENERATE TOKEN

This function allows with valid credentials (http basic authorization) to gain a valid token usable with the other operations. To be able to use the web services is mandatory to add some headers in the call; in the generate Token the headers are:

- Accept: application/json
- Authorization: Basic (USERNAME:PASSWORD base 64 encoded)
- forcenew: true (default true) If set to true the token will be regenerated, otherwise the service will return the active one, if exists.

The obtained token is valid for 24 hours.

Each account may have only 1 token valid at the same time; each time a new one gets generated the old one becomes invalid. To avoid any problem with multiples entities using the same service, you can set the "forcenew" field to false in the request to avoid the generation of a new token each time.

---

### URL

<https://ws3.sanmarinomail.it/SmmWs3/token>

---

### ↑ REQUEST EXAMPLE

```
curl -H "Accept: application/json" -H "Authorization: Basic YWxhZGRpbjpvYVuc2VzYW11" -H "forcenew: false" -X POST https://ws3.sanmarinomail.it/SmmWs3/token
```

---

### ↓ RESPONSE EXAMPLES

#### ERROR:

```
{
  "errorDescription": "Username or Password Not Valid",
  "errorCode": 3001,
  "status": -1
}
```

#### SUCCESSFUL (STATUS FIELD = 0):

```
{
  "token": "{token}d87bb9c6-25fa-4035-ae90-c515554f3cf2",
  "status": 0
}
```

## CREATE SHIPMENT

This operation allows you to book a shipment and retrieve the corresponding label.

PLEASE NOTE TO UPLOAD ANY NEEDED FILE BEFORE  
CALLING THE GENERATE LABEL REQUEST

(see specific upload method information).

The shipment references for the label to be retrieved must be provided as a JSON string.

All fields accepted by the request are listed in Table 1 and Table 2 Table 1 and Table 2.

If the `SMM_PRODUCT_CODE` (optional) field is set, it will be used to identify the SMM product to be used; otherwise, the SMM Algorithm will need to determine the product automatically.

For extra-CEE shipments or shipments containing dangerous goods, all fields in the package object are mandatory.

For multi-parcel shipments, that require parcel-specific information (e.g., UPS, DHL), the `MULTI_PARCEL` field must be set to 1, and a separate *Json Array* must be populated with all parcel details (see example below).

The options available (not mandatory) are:

- `force_reprint_if_exists`: (default value: false): if a label (with same reference) already exists and the field is set to false the system will answer with "Reference already used" error otherwise if set to true the system will send the previously generated label.
- `delete_if_exists`: (default value: false): if the label already exists and the field is set to true the existing label will be deleted, and a new one will be generated.
- `base64`: (default value: false): if set to true, the output of ZPL label will be encoded in Base64, otherwise will be sent in plain text.

The optional json object "mirror" will be added to the response as received

### MIRROR STRUCTURE USAGE

You can use the `mirror` Json structure by filling it with the fields required for recognition. The structure will be returned unchanged in the response.

 URL

<https://ws3.sanmarinomail.it/SmmWs3/createshipment>

## JSON EXAMPLE

```
{
  "shipment": {
    "CLIENT_SHIP_REF": "TEST_NEW_WS_001",
    "SMM_CUST_CODE": "ITIT0000999",
    "DELIVERY_NAME": "Mario Rossi",
    "DELIVERY_ADDR": "via Farini 81",
    "DELIVERY_CITY": "Milano",
    "DELIVERY_ZIP_CODE": "20159",
    "WEIGHT": 12,
    "DEL_ISO_COUNTRY_CODE": "IT",
    "PRE_ALERT_DATE": "2020-07-20",
    "DELIVERY_DISTRICT": "MI"
  },
  "options": {
    "force_reprint": false,
    "confirmed": false,
    "delete_if_exists": false,
    "base64": true
  },
  "mirror": {
    "cod_attivita_infolog": "temp",
    "field1": "temp2"
  }
}
```

## ↑ CURL EXAMPLE

```
curl -H "Accept: application/json" -H "token: {token}TEST-TOKEN-a0a2-47b0-
blab-923d2ec4b8ce" -H "username: testusername" -d '{"CLI-
ENT_SHIP_REF": "testreference", "SMM_CUST_CODE": "TEST_ID", "base64": false}.....
.....{ "shipment":{ "CLIENT_SHIP_REF": "TEST_NEW_WS_002",
"SMM_CUST_CODE": "ITIT0000999", "DELIVERY_NAME": "Mario Rossi", "DELIV-
ERY_ADDR": "via farini 81", "DELIVERY_CITY": "Milano", "DELIV-
ERY_ZIP_CODE": "20159", "WEIGHT": 12, "DEL_ISO_COUNTRY_CODE": "IT",
"PRE_ALERT_DATE": "2020-07-13", "DELIVERY_DISTRICT": "MI" }, "op-
tions":{ "force_reprint_if_exists": false, "confirmed": false, "de-
lete_if_exists": false, "base64": true }, "mirror":{ "field1": "temp" } }'
-X POST
http://localhost:8080//retrievelabelhttps://ws3.sanmarinomail.it/SmmWs3/creat
eshipment
```

## ↓ RESPONSE EXAMPLES

### ✘ ERROR:

```
{
  "errorDescription": "Token Not Valid",
  "errorCode": 3002,
  "status": -1
}
```

### ✘ ERROR:

```
{
  "mirror": {
    "cod_attivita_infolog": "temp",
    "cod_stazione": "temp2"
  }
}
```

```

    },
    "CLIENT_SHIP_REF": "TEST_NEW_WS_003",
    "notes": "",
    "errorDescription": "Error Reference number already used",
    "errorCode": 1063,
    "label":
    ""^XA~TA000~JSN^LT0^MNV^MTD^PON^PMN^LH0,0^JMA^PR4,4~SD15^JUS^LRN^CIO^XZ ^XA
    ^MMT ^PW799 ^LL1199 ^LS0 ^FT753,776^A0I,49,36^FH\\^FDSAN MARINO MAIL ITALIA
    SRL^FS ^FO269,741^GB519,0,8^FS ^FT728,694^A0I,28,28^FH\\^FDATTENTION ^FS
    ^FT725,645^A0I,28,28^FH\\^FDIF YOU RECEIVE THIS LABEL^FS
    ^FT725,597^A0I,28,28^FH\\^FDPLEASE CALL +39900266227799^FS
    ^FT634,553^A0I,28,28^FH\\^FDOPS DEPT^FS ^FT733,498^A0I,28,28^FH\\^FDE-MAIL
    OPS@SANMARINOMAIL.IT^FS ^FWB ^BY3,3,160 ^FO55,50^BC^FD#ICR#^FS ^PQ1,0,1,Y
    ^FVN ^XZ",
    "status": -1
  }
}

```

### ✘ ERROR:

```

{
  "errorDescription": "Error parsing json input - org.json.JSONException: Ex-
  pected a ':' after a key at 103 [character 104 line 1]",
  "errorCode": 999,
  "status": -1
}

```

### ✔ SUCCESSFUL (STATUS FIELD = 0):

```

{
  "MASTER_USN_PARCEL_NR": "465162803",
  "mirror": {
    "field1": "temp"
  },
  "CLIENT_SHIP_REF": "TEST_NEW_WS_004",
  "notes": "",
  "Haulier": "GLS",
  "USN_PARCEL_NUMBER": "600256057",
  "label": ""^XA ^LH0,0 ^FO4,2 ^GB804,798,4 ^FS ^FO4,2 ^GB548,52,4 ^FS
  ^FO19,12 ^ADN,36,20 ^FDTEST WEBSERVICE ^FS ^FO548,2 ^GB260,52,4 ^FS ^FO561,16
  ^ADN,36,10 ^FDP/V ^FS ^FO611,16 ^ADN,36,10 ^FD1:3 ^FS ^FO693,16 ^ADN,36,10
  ^FD22/07/20 ^FS ^FO21,48 ^ADN,170,60 ^FDBOLLATE ^FS ^FO593,48 ^ADN,170,60
  ^FD99 ^FS ^FO15,185 ^AQN,10,10 ^FDPer info sul trattamento dati personali
  www.gls-italy.com/privacydest ^FS ^FO4,210 ^GB128,166,4 ^FS ^FO128,210
  ^GB680,166,4 ^FS ^FO136,220 ^ADN,36,15 ^FDMario Rossi ^FS ^FO136,276
  ^ADN,36,10 ^FDvia farini 81 ^FS ^FO15,243 ^ADN,108,50 ^FDLD ^FS ^FO136,338
  ^ADN,36,14 ^FDMilano ^FS ^FO580,338 ^ADN,36,15 ^FDMI ^FS ^FO632,210
  ^GB176,166,4 ^FS ^FO640,220 ^ADN,18,5 ^FDSEDI CONTIGUE ^FS ^FO695,246
  ^ADN,18,5 ^FDSCN ^FS ^FO632, 273 ^GB176,103,4 ^FS ^FO640,280 ^ADN,18,5
  ^FDPeso Kg ^FS ^FO680,318 ^ADN,36,20 ^FD12.0 ^FS ^FO632, 372 ^GB176,48,4 ^FS
  ^FO640,378 ^ADN,18,5 ^FDPorto: ^FS ^FO658,398 ^ADN,18,10 ^FDFRANCO ^FS
  ^FO4,372 ^GB804,48,4 ^FS ^FO25,383 ^ADN,36,10 ^FDNote: ^FS ^FO88,383
  ^ADN,36,10 ^FD ^FS ^FO640,650 ^XGE:GLSMINI.GRF,1,1 ^FS ^FO606,718 ^GB202,82,4
  ^FS ^FO4,718 ^GB606,82,4 ^FS ^FO50,422 ^BY3 ^BCN,260,N,N,N,A
  ^FVL2600256057010M451^FS ^FO100,687 ^AAN,26,16 ^FDL2 60025605701 0 M451 01
  ^FS ^XZ",
  "status": 0
}

```

## 📄 MULTIPARCEL JSON REQUEST EXAMPLE:

```
{
  "shipment": {
    "CLIENT_SHIP_REF": "TEST_NEW_WS_001",
    "SMM_CUST_CODE": "ITIT0000999",
    "DELIVERY_NAME": "Mario Rossi",
    "DELIVERY_ADDR": "via Farini 81",
    "DELIVERY_CITY": "Milano",
    "DELIVERY_ZIP_CODE": "20159",
    "WEIGHT": 3,
    "DEL_ISO_COUNTRY_CODE": "IT",
    "PRE_ALERT_DATE": "2020-07-20",
    "DELIVERY_DISTRICT": "MI",
    "MULTI_PARCEL": 1,
    "packages": [
      {
        "WEIGHT": 1,
        "DIMEN_PCS_HEIGHT": 10,
        "DIMEN_PCS_LENGTH": 11,
        "DIMEN_PCS_WIDTH": 12
      },
      {
        "WEIGHT": 2,
        "DIMEN_PCS_HEIGHT": 20,
        "DIMEN_PCS_LENGTH": 21,
        "DIMEN_PCS_WIDTH": 22
      }
    ]
  },
  "options": {
    "force_reprint": false,
    "confirmed": false,
    "delete_if_exists": false,
    "base64": true
  }
}
```

## ↓ MULTIPARCEL RESPONSE EXAMPLES

### ✅ SUCCESSFUL (STATUS FIELD = 0):

```
{
  "MASTER_USN_PARCEL_NR": "1ZXXXXXXXXXXXXXXXXXX",
  "CLIENT_SHIP_REF": "TESTMC3_05120006",
  "notes": "",
  "SMM_CUST_CODE": "ITIT0000999",
  "SMM_PRODUCT_CODE": "INT_UPS_EXPRESS",
  "packages": [
    {
      "MASTER_USN_PARCEL_NR": "TESTMC3_05120006",
      "CLIENT_SHIP_REF": "TESTMC3_05120006",
      "USN_PARCEL_NUMBER": "1ZXXXXXXXXXXXXXXXXXX",
      "label":
        "C15YQQ0KXkxSTg0KXk1OWQ0KXk1GTixODQpeTEgxmCwxMg0KXk1DWQ0KX1BPSQ0KX1BXODEyDQpe
        Q0kyNw0KXkzPMTUsN15BME4sMjAsMjReRlZDTElFTlRFIFRFU1ReRlMN.....peWFoNCg=="
    },
    {
      "MASTER_USN_PARCEL_NR": "TESTMC3_05120006",
      "CLIENT_SHIP_REF": "TESTMC3_05120006",

```

```

        "USN_PARCEL_NUMBER": "1XXXXXXXXXXXXXXXXX",
        "label":
"C15YQQ0KXkxSTg0KXk1OWQ0KXk1GTixODQpeTEgxFCwMg0KXk1DWQ0KX1BPSQ0KX1BXODEyDQpe
Q0kyNw0KXkZPMTUsN15BME4sMjAsMjReRlZDTElFTlRFIFRFU1ReRlMNC15GTzE1LDI3XkEwTiwyM
CwyNF5GVjAyNjYyMjc3OTleRlMNC15GTzE1LDQ3XkEwTiwyMCwyNF5GVkNMSUVOVEUgVEVTVF5GUw
0KXkZPMTUsNjdeQTBOLDIwLDI0XkZWVklBIENB.....KXkRODQpeWFOncg=="
    }
  ],
  "Haulier": "PAITITINT0999",
  "status": 0
}

```

#### DROPOFF JSON REQUEST EXAMPLE:

```

{
  "shipment": {
    "DELIVERY_POINTRELAYID": "IT-PDB-RTZ-Z6076",
    "CLIENT_SHIP_REF": "TestDrop0007N",
    "DELIVERY_EMAIL": "ict.smm@sanmarinomail.it",
    "DELIVERY_MOBILE_PH": "9994602892",
    "DELIVERY_NAME": "ICT",
    "DELIVERY_NAME_2": "",
    "DELIVERY_PHONE_NR": "",
    "DEL_ISO_COUNTRY_CODE": "IT",
    "LDV_PRINTING": 1,
    "NR_OF_PCS": 1,
    "OUTPUT_TYPE": 0,
    "PRE_ALERT_DATE": "2024-10-24",
    "SMM_CUST_CODE": "ITIT0000999",
    "MULTI_PARCEL": 0,
    "packages": [
      {
        "WEIGHT": 3.98,
        "DIMEN_PCS_HEIGHT": 34.0,
        "DIMEN_PCS_LENGTH": 39.0,
        "DIMEN_PCS_WIDTH": 28.0,
        "TOT_VOLUME": 0.0,
        "CLIENT_SHIP_REF": "TestDrop0007N"
      }
    ]
  },
  "options": {
    "force_reprint_if_exists": false,
    "confirmed": false,
    "delete_if_exists": false,
    "base64": true
  },
  "mirror": {
    "field1": "temp"
  }
}

```

## ↓ DROPOFF JSON RESPONSES:

**✗ ERROR;**

```
{
  "mirror": {
    "field1": "temp"
  },
  "CLIENT_SHIP_REF": "TestDrop0008N",
  "notes": "",
  "errorDescription": "Error generating label Cannot get dropoff finfor-
mation",
  "SMM_CUST_CODE": "ITIT0000999",
  "errorCode": 999,
  "label": "XlhBDQoNC15GW.....",
  "SMM_PRODUCT_CODE": "IT_PDBEXPXL_DROPOFF",
  "Haulier": "PAITITPDB0050",
  "status": -1
}
```

**✓ SUCCESSFUL (STATUS FIELD = 0):**

```
{
  "MASTER_USN_PARCEL_NR": "TestDrop0007N",
  "mirror": {
    "field1": "temp"
  },
  "CLIENT_SHIP_REF": "TestDrop0007N",
  "notes": "",
  "SMM_CUST_CODE": "ITIT0000999",
  "USN_PARCEL_NUMBER": "3UX000X000001",
  "label": "XlhBCgpeRk8zMCw4MjVeR0ZBLDM5MzYsMzkzNiwxNiwsOjo6Ojo6Ojo.....",
  "SMM_PRODUCT_CODE": "IT_PDBXXX_DROPOFF",
  "Haulier": "PAITITPDB0050",
  "status": 0
}
```

## GET LABEL

This operation allows you to retrieve a label for a referenced shipment; to be able to gain access is mandatory to have a valid token. The shipment reference for the label to retrieve must be passed as JSON string.

Mandatory fields are:

- SMM\_CUST\_CODE: San Marino Mail client id (string)
- CLIENT\_SHIP\_REF: shipment reference (string)

Optional fields are:

- base64: ask for a label string encoded in base64 or not; (Boolean default is true)

### URL

<https://ws3.sanmarinomail.it/SmmWs3/retrievelabel>

### JSON REQUEST EXAMPLE:

```
{
  "CLIENT_SHIP_REF": "testreference",
  "SMM_CUST_CODE": "TEST_ID",
  "base64": false,
  "mirror": {
    "cod_attivita_infolog": "temp",
    "cod_stazione": "temp2"
  }
}
```

### ↑ CURL EXAMPLE

```
curl -H "Accept: application/json" -H "token: {token}TEST-TOKEN-a0a2-47b0-b1ab-923d2ec4b8ce" -H "username: testusername" -d '{"CLIENT_SHIP_REF": "testreference", "SMM_CUST_CODE": "TEST_ID", "base64": false...}' -X POST http://localhost:8080//retrievelabelhttps://ws3.sanmarinomail.it/SmmWs3/retrievelabel
```

### ↓ RESPONSE EXAMPLES:

```
✘ Error:
{
  "errorDescription": "No shipments found for reference testreference",
  "errorCode": 1031,
  "status": -1,
  "mirror": {
    "cod_attivita_infolog": "temp",
    "cod_stazione": "temp2"
  }
}
```

**✓ SUCCESSFUL (STATUS FIELD = 0):**

```
{
  "CLIENT_SHIP_REF": "testreference",
  "SMM_CUST_CODE": "TEST_ID",
  "label": "^XA^PON^PQ1^Mud^PW79.....Special Instruction:^FS^XZ",
  "status": 0,
  "usn": "xxx",
  "mirror": {
    "cod_attivita_infolog": "temp",
    "cod_stazione": "temp2"
  }
}
```

## DELETE LABEL

This operation allows to delete a generated label; to be able to gain access is mandatory to have a valid token.

The shipment reference for the label to delete must be passed as JSON string.

Mandatory fields are:

- SMM\_CUST\_CODE: San Marino Mail client id (string)
- CLIENT\_SHIP\_REF: shipment reference (string)

---

### URL

`https://ws3.sanmarinomail.it/SmmWs3/deleteLabel`

---

### JSON REQUEST EXAMPLE:

```
{
  "CLIENT_SHIP_REF": "testreference",
  "SMM_CUST_CODE": "TEST_ID"
}
```

---

### ↑ CURL EXAMPLE

```
curl -H "Accept: application/json" -H "token: {token}TEST-TOKEN-a0a2-47b0-b1ab-923d2ec4b8ce" -H "username: testusername" -d '{"CLIENT_SHIP_REF": "testreference", "SMM_CUST_CODE": "TEST_ID..."' -X POST http://localhost:8080//https://ws3.sanmarinomail.it/SmmWs3/deleteLabel
```

---

### ↓ RESPONSE EXAMPLES:

#### ERROR:

```
{
  "CLIENT_SHIP_REF": "TEST_NEW_WS_003",
  "errorDescription": "no label to delete with reference TEST_NEW_WS_003",
  "errorCode": 3003,
  "status": -1
}
```

#### SUCCESSFUL (STATUS FIELD = 0):

```
{
  "CLIENT_SHIP_REF": "TEST_NEW_WS_004",
  "notes": "Label deleted successfully",
  "SMM_CUST_CODE": "ITIT0000999",
  "status": 0
}
```

## MANIFEST

This operation allows you to confirm a list of shipments and retrieve a PDF report in Base64 format.

To use this web service, it is mandatory to include certain headers in the request. The request must be passed as JSON string.

Mandatory fields are:

- SMM\_CUST\_CODE: San Marino Mail client id (string)
- CLIENT\_SHIP\_REF\_LIST: shipment reference list json array

### URL

<https://ws3.sanmarinomail.it/SmmWs3/manifest>

### JSON REQUEST EXAMPLE:

```
{
  "manifest": {
    "SMM_CUST_CODE": "ITIT0000999",
    "CLIENT_SHIP_REF_LIST": [
      "TEST_NEW_WS_003",
      "TEST_NEW_WS_004"
    ]
  }
}
```

### CURL EXAMPLE

```
curl -H "Accept: application/json" -H "token: {token}TEST-TOKEN-a0a2-47b0-b1ab-923d2ec4b8ce" -H "username: testusername" -d '{ "manifest": { "SMM_CUST_CODE": "ITIT0000999", "CLIENT_SHIP_REF_LIST": ["TEST_NEW_WS_003","TEST_NEW_WS_004"]}}' -X POST https://ws3.sanmarinomail.it/SmmWs3/manifest
```

### RESPONSE EXAMPLES:

#### ERROR:

```
{
  "errorDescription": "Error No shipments to be manifested",
  "errorCode": 1065,
  "status": -1
}
```

#### SUCCESSFUL (STATUS FIELD = 0):

```
{
  "SMM_CUST_CODE": "ITIT0000999",
  "manifestPdf":
  "JVBERi0xLjQKJfbk/N8KMSAwIG9iago8PAovVHlwZSAvQ2F0YWxvZ.....",
  "status": 0
}
```

## DOCUMENT UPLOAD

This operation allows you to upload a file (in base64 format) related to a shipment. When using the "Create Shipment" method populating with value 1 the "DOCUMENTS\_NEEDED" field, every document related to the shipment (related to the CLIENT\_SHIP\_REF field) will be uploaded to the carrier. The request must be passed as JSON string.

PLEASE NOTE: UPLOAD ALL THE FILES  
BEFORE CALLING THE GENERATE LABEL REQUEST

Mandatory fields are:

- action: **"UPLOAD"**
- SMM\_CUST\_CODE: San Marino Mail client id (string)
- CLIENT\_SHIP\_REF: shipment reference
- category: document category (see list below)
- documentdata64: base64 encoding string of file
- filename: filename
- filetype: filetype (ex. pdf, tiff, png, ...)

Optional Fields:

SMMProductCode

Document category list:

	SMM_code	DESCRIPTION
1	PDC001	Commercial invoice
2	PDC002	CIN Commercial invoice
3	PDC003	Pro forma invoice
4	PDC004	Certificate of origin
5	PDC005	NAFTA certificate
6	PDC006	Custom Declaration
7	PDC007	HWB
8	PDC008	OTHER
9	PDC009	ETD
10	PDC010	AUTH FORM
11	PDC011	Export Accompanying doc
12	PDC012	Export License
13	PDC013	Import Permit
14	PDC014	Power of Attorney
15	PDC015	Packing list
16	PDC016	Sed document
17	PDC017	shipper letter of instruction
18	PDC018	USMCA Commercial Invoice
19	PDC019	USMCA Certification of Origin

 URL

<https://ws3.sanmarinomail.it/SmmWs3/documents>

 JSON REQUEST EXAMPLE:

```
{
  "document": {
    "action": "upload",
    "SMM_CUST_CODE": "ITIT0000999",
    "CLIENT_SHIP_REF": "TEST_PPP2",
    "category": "0B",
    "filename" : "test.pdf",
    "filetype" : "pdf",
    "documentdata64":
    "JVBERi0xLjYNJeLjz9MNCjM3IDAgb2JqIDw8L0xpbnVhcmcl6ZWQgMS9MIDIwNTk3L08gNDAvRSAx
    NDExNS9OIDEvVCAxOTc5NS9II...."
  }
}
```

---

## ↑ CURL EXAMPLE

```
curl -H "Accept: application/json" -H "token: {token}TEST-TOKEN-a0a2-47b0-b1ab-923d2ec4b8ce" -H "username: testusername" -d '{
  "document": {
    "SMM_CUST_CODE": "ITIT0000999",
    "CLIENT_SHIP_REF": "TEST_PPP2",
    "category": "0B",
    "filename": "test.pdf",
    "filetype": "pdf",
    "documentdata64":
    "JVBERi0xLjYNJeLjz9MNCjM3IDAgb2JqIDw8L0xpbmVhcml6ZWQgMS9MIDIwNTk3L08gNDAvRSAx
    NDExNS90IDEvVCAxOTc5NS9II...." } }' -X POST
https://ws3.sanmarinomail.it/SmmWs3/documentupload
```

---

## ↓ RESPONSE EXAMPLES:

### ERROR:

```
{
  "errorDescription": "missing mandatory fields",
  "errorCode": 3030,
  "status": -1
}
```

### SUCCESSFUL (STATUS FIELD = 0):

```
{
  "CLIENT_SHIP_REF": "TEST_doc",
  "SMM_CUST_CODE": "ITIT0000999",
  "DOCUMENT_ID": "ITIT0000999_00000000003",
  "category": "0B",
  "status": 0
}
```

## DOCUMENT DELETE

This operation allows you to delete a previously uploaded file. The request must be passed as JSON string

Mandatory fields are:

- `action`: "**DELETE**"
- `SMM_CUST_CODE`: San Marino Mail client id (string)
- `CLIENT_SHIP_REF`: shipment reference
- `DOCUMENT_ID`: identificativo documento ricevuto in risposta alla chiamata di upload

### URL

`https://ws3.sanmarinomail.it/SmmWs3/documents`

### JSON REQUEST EXAMPLE:

```
{
  "document": {
    "action": "delete",
    "SMM_CUST_CODE": "ITIT0000999",
    "CLIENT_SHIP_REF": "TEST_PPP2",
    "DOCUMENT_ID": "ITIT0000999_000000000003"
  }
}
```

### ↑ CURL EXAMPLE

```
curl -H "Accept: application/json" -H "token: {token}TEST-TOKEN-a0a2-47b0-b1ab-923d2ec4b8ce" -H "username: testusername" -d 'MISSING' -X POST
https://ws3.sanmarinomail.it/SmmWs3/documentupload
```

### ↓ RESPONSE EXAMPLES:

#### ERROR:

```
{
  "errorDescription": "missing mandatory fields",
  "errorCode": 3030,
  "status": -1
}
```

#### SUCCESSFUL (STATUS FIELD = 0):

```
{
  "CLIENT_SHIP_REF": "TEST_doc",
  "SMM_CUST_CODE": "ITIT0000999",
  "DOCUMENT_ID": "ITIT0000999_000000000003",
  "category": "0B",
  "status": 0
}
```

## TRACKING

This operation allows you to retrieve all the events for a referenced shipment; to be able to gain access is mandatory to have a valid token. The shipment reference for tracking service must be passed as JSON string:

Mandatory fields are:

- **CLIENT\_SHIP\_REF**: Shipment reference (string) or **USN**: shipment (string)
- **SMM\_CUST\_CODE**: San Marino Mail client id (string)

### URL

<https://ws3.sanmarinomail.it/SmmWs3/tracking>

### JSON REQUEST EXAMPLE:

```
{
  "clientshipref": "testreference",
  "SMM_CUST_CODE": "TEST_ID"
}
```

### ↑ CURL EXAMPLE

```
curl -H "Accept: application/json" -H "token: {token}TEST-TOKEN-a0a2-47b0-
blab-923d2ec4b8ce" -H "username: testusername" -d '{"client-
shipref":"testreference","SMM_CUST_CODE": "TEST_ID"}' -X POST
https://ws3.sanmarinomail.it/SmmWs3/tracking
```

### ↓ RESPONSE EXAMPLES:

#### ERROR:

```
{
  "errorDescription": "Shipment not found",
  "errorCode": 3003,
  "status": -1
}
```

#### SUCCESSFUL (STATUS FIELD = 0):

```
{
  {
    "usn": "XXXXXXXXXXXXXXXXXX",
    "country": "United Kingdom",
    "productCode": "GGGGGGGGG",
    "invoiceecustref": "testreference",
    "countryiso": "GB",
    "clientshipref": "testreference",
    "status": 0,
    "events": [
      {
        "date": "06/12/19",
        "eventcode": "104",
        "eventdescription": "shipment has been delivered",
        "time": "12:14",
        "eventname": "delivered"
      }
    ]
  }
}
```

```
    },
    {
      "date": "06/12/19",
      "eventcode": "141",
      "eventdescription": "shipment has been given to driver for de-
livery",
      "time": "09:20",
      "eventname": "out for delivery"
    },
    ...
    {
      "date": "28/11/19",
      "eventcode": "0",
      "eventdescription": "shipment has been pre alerted by sender",
      "time": "15:14",
      "eventname": "shipment booked"
    }
  ]
}
```

## ANNEXES

Here's a list of all available fields related to the shipment (to be passed on in the json object "shipment"):

NAME	DESCRIPTION	TYPE	BYTE	MAND.	NOTE
SMM_CUST_CODE	<i>Company Id</i>	T	20	Y	
SMM_PRODUCT_CODE	<i>Product code</i>	T	50	N	
PRE_ALERT_DATE	<i>Pre alert Date</i>	T	10	N	(yyyy-MM-dd)
CLIENT_SHIP_REF	<i>Client Shipment Reference</i>	T	35	Y	
USN_PARCEL_NUMBER	<i>USN parcel number</i>	T	50	N	
MASTER_USN_PARCEL_NR	<i>Master USN</i>	T	30	N	
DELIVERY_NAME	<i>Delivery Name</i>	T	35	Y	
DELIVERY_STR_TYPE	<i>Delivery Street type</i>	T	30	N	
DELIVERY_ADDR	<i>Delivery address 1</i>	T	35	Y	
DELIVERY_ADDR_NO	<i>Delivery address No</i>	T	5	N	
DELIVERY_ZIP_CODE	<i>Delivery Zip code</i>	T	12	Y	
DELIVERY_CITY	<i>Delivery City</i>	T	50	Y	
DELIVERY_DISTRICT	<i>Delivery district (Mandatory for italy)</i>	T	50	Y/N	
DEL_ISO_COUNTRY_CODE	<i>Delivery iso country</i>	T	3	Y	
NR_OF_PCS	<i>Number of items</i>	N	10	Y	
WEIGHT	<i>Weight in KG</i>	N	10	Y	
PACKAGING_TYPE	<i>Packaging type</i>	T	40	N	
LDV_PRINTING	<i>Ldv printing (1, 0) (default 0)</i>	N	1	N	
ADDRESS_CLEANING	<i>Address cleaning (1,0)</i>	N	1	N	
CUST_SERVICE_ACTIVITY	<i>Customer service (1,0)</i>	N	1	N	
WAREHOUSE_TRANSIT	<i>Warehouse Transit (1,0)</i>	N	1	N	
PARCEL	<i>Parcel Number</i>	N	10	Y	
SMS_PREADVISE_REQUEST	<i>SMS preadvise</i>	N	1	N	

EMAIL_PREADVISE_REQUEST	Email preadvise	N	1	N	
CLIENT_SHIP_REF_2	Client Shipment reference 2	T	35	N	
DELIVERY_NAME_2	Delivery name 2	T	35	N	
DELIVERY_ADDR_2	Delivery address 2	T	35	N	
DELIVERY_ADDR_3	Delivery address 3	T	35	N	
DELIVERY_ADDR_4	Delivery address 4	T	35	N	
DELIVERY_PHONE_NR	Delivery phone number	T	50	N	
DELIVERY_FAX_NR	Delivery fax number	T	50	N	
DELIVERY_MOBILE_PH	Delivery mobile phone	T	50	N	
DELIVERY_EMAIL	Delivery email	T	50	N	
DELIVERY_INSTRUCTION	Delivery Instruction	T	150	N	
DELIVERY_ADDRESS_ID	Delivery address Id	T	12	N	
DELIVERY_FISCAL_CODE	Delivery fiscal code	T	50	N	
DELIVERY_SATURDAY	Delivery saturday (1,0)	N	1	N	
DIMEN_PCS_LENGTH	Length	N	10	N	
DIMEN_PCS_WIDTH	Width	N	10	N	
DIMEN_PCS_HEIGHT	Height	N	10	N	
TOT_VOLUME	Total volume	N	10	N	
DECLARED_GOODS_VALUE	Declared goods value	N	10	N	
CUST_VALUE_CURRENCY	Value currency	T	10	N	
SENDER_VAT_NUMBER	VAT number	T	50	N	
SENDER_DOCUMENT_NR	Document Nr	T	50	N	
INVOICE_NR_FOLLOWING	Invoice Nr	T	50	N	
COD_AMOUNT	COD amount (otherwise 0)	N	10	N	
COD_PAYM_METHOD	COD Payment method (CON)	T	50	N	
COD_CURRENCY	COD currency	T	10	N	
INSURANCE_VALUE	Insurance value	N	10	N	
INSURANCE_CURRENCY	Insurance currency	T	10	N	

PICKUP_NAME	Pickup name	T	50	N	
PICKUP_NAME2	Pickup name 2	T	50	N	
PICKUP_ADDR	Pickup address 1	T	100	N	
PICKUP_ADDR_NO	Pickup address No	T	5	N	
PICKUP_ADDR_2	Pickup address 2	T	100	N	
PICKUP_ADDR_3	Pickup address 3	T	100	N	
PICKUP_ADDR_4	Pickup address 4	T	100	N	
PICKUP_ZIP_CODE	Pickup zipcode	T	10	N	
PICKUP_CITY	Pickup city	T	50	N	
PICKUP_PHONE_NR	Pickup phone nr	T	50	N	
PICKUP_FAX_NR	Pickup fax nr	T	50	N	
PICKUP_MOBILE_PH	Pickup mobile nr	T	50	N	
PICKUP_EMAIL	Pickup email	T	50	N	
PICKUP_ISO_COUNTRY_CODE	Pickup ISO country	T	3	Y	
PICKUP_ADDR_ID	Pickup address Id	T	12	N	
DELIVERY_AT_FLOOR	Delivery at floor (1,0)	N	1	N	
DELIVERY_APPOINTMENT	Delivery appointment (1,0)	N	1	N	
DELIVERY_EVENING	Delivery evening (1,0)	N	1	N	
PICKUP_USED_RAE	Used RAE (1,0)	N	10	N	
PICKUP_DATE	Pickup date	T	10	N	(yyyy-MM-dd)
OPENING_HOUR_MORNING	Opening hour morning	N	1	N	
CLOSING_HOUR_MORNING	Closing hour morning	N	1	N	
OPENING_HOUR_AFTERNOON	Opening afternoon	N	1	N	
CLOSING_HOUR_AFTERNOON	Closing afternoon	N	1	N	
PICKUP_WINDOW	Pickup window	T	2	N	
PICKUP_DISTRICT	Pickup district	T	2	N	
CONTENT	Content type	T	50	N	
GOODS_VALUE	Commercial value	N	10	N	

GOODS_CURRENCY	Commercial currency	T	3	N	
CUSTOM_CODE	Customs code	T	12	N	
OUTPUT_TYPE	OutputType (0=ZPL,1=PDF)	N	1	Y	
DELIVERY_GDO	GDO delivery	N	1	N	
DELIVERY_NDS	Neutral delivery service	N	1	N	
MULTI_PARCEL	set to 1 for multiparcel shipment (default 0)	N	1	N	
NR_OF_PARCELS	Number of parcels	N	10	N	
RETURN_LABEL	return label needed	N	1	N	
RETURN_PRODUCT_CODE	Return label Product code	T	50	N	
DOCUMENTS_NEEDED	set to 1 if previously uploaded documents must be sent to the carrier (default 0)	N	1	N	
DELIVERY_POINTRELAYID	Dropoff id point	T	50	*	N for Home Delivery, Y for Dropoff delivery

Table 1 – createShipment available Fields

Here's a list of all available fields related to the parcel (to be passed in the json object "packages"):

NAME	DESCRIPTION	TYPE	BYTE	MAND.	NOTE
CLIENT_SHIP_REF	<i>Client Shipment Reference</i>	T	35	N	
WEIGHT	<i>Weight in KG</i>	N	10	Y	
DIMEN_PCS_LENGTH	<i>Length</i>	N	10	Y	
DIMEN_PCS_WIDTH	<i>Width</i>	N	10	Y	
DIMEN_PCS_HEIGHT	<i>Height</i>	N	10	Y	
CONTENT	<i>Content type</i>	T	50	N	
COD_AMOUNT	<i>COD amount</i>	N	10	N	(otherwise 0)
COD_PAYM_METHOD	<i>COD Payment method (CON)</i>	T	50	N	
COD_CURRENCY	<i>COD currency</i>	T	10	N	
INSURANCE_VALUE	<i>Insurance value</i>	N	10	N	
INSURANCE_CURRENCY	<i>Insurance currency</i>	T	10	N	
GOODS_VALUE	<i>Commercial value</i>	N	10	N	
GOODS_CURRENCY	<i>Commercial currency</i>	T	3	N	
HAZMAT	<i>Hazardous goods</i>	N	1	N	
HAZMAT_CLASS	<i>Hazardous goods class UN (es. LQ)</i>	T	20	N	
HAZMAT_SHIPPING_NAME	<i>The Proper Shipping Name assigned by ADR, CFR or IATA.</i>	T	50	N	
HAZMAT_REGULATION_SET	<i>Hazardous goods The Regulatory set (ex ADR)</i>	T	5	N	
INCOTERMS	<i>Incoterms</i>	T	20	N	
HS_CODE	<i>HS Code</i>	T	20	N	
INVOICE_NR_DATE	<i>Invoice date</i>	T	10	N	(yyyy-MM-dd)
NR_PIECES_HAZ	<i>Item Quantity of Hazardous goods</i>	N	10	N	
INVOICE_NR	<i>Invoice Number</i>	T	30	N	
HAZMAT_UOM	<i>The unit of measure used for the mass capacity of the regulated good.</i>	T	15	N	<i>For Example: ml, L, g, mg, kg, cylinder, pound, pint, quart, gallon, ounce</i>
HAZ-	<i>This is the hazard class associated to</i>	N	1	N	

MAT_ClassDivisionNumber	<i>the specified commodity.</i>				
HAZ- MAT_ChemicalRecordIdentifier	<i>Should be set to 1</i>	N	1	N	
HAZMAT_PackagingType	<i>The type of package used to contain the regulated good. (Ex: Fiberboard Box). Required if CommodityRegulatedLevelCode = LQ or FR</i>	T	255	N	<i>Ex. FIBERBOARD BOX, WOOD(EN) BOX, PLASTIC JERRICAN, METAL BOX, STEEL DRUM, OTHER, PLASTIC BOX, PLASTIC DRUM, STYROFOAM BOX, CYLINDERS, ENVIROTAINER, PLYWOOD BOX, ALUMINUM DRUM, ALUMINUM CYLINDERS, PLASTIC PAIL, PLYWOOD DRUM, FIBER DRUM, STEEL JERRICAN, ALUMINUM JERRICAN, STEEL BOX, CARTON, ALUMINUM BOX</i>
HAZMAT_IDNumber	<i>This is the ID number (UN/NA/ID) for the specified commodity. Required if CommodityRegulatedLevelCode = LR, LQ or FR and if the field applies to the material by regulation.</i>	T	6	N	<i>UN/NA/ID Identification Number assigned to the specified regulated good. (Include the UN/NA/ID as part of the entry).</i>
HAZMAT_TransportationMode	<i>Not applicable for ADR regulation set. Required for any other regulation set. Declares that a package was prepared according to ground passenger aircraft or cargo aircraft only.</i>	T	30	N	<i>Valid values: Highway=Highway Ground=Ground PAX=Passenger Aircraft Passenger Aircraft=Passenger Aircraft CAO=Cargo Aircraft Only Cargo Aircraft Only=Cargo Aircraft Only Valid entries include: Highway, Ground, PAX, Passenger Aircraft, CAO and Cargo Aircraft Only.</i>

Table 2 - createShipments packages Fields